



SAE 10W-30 API SN/ILSAC GF-5 FULL SYNTHETIC Oil

DESCRIPTION:

Olympic Petroleum's 10W-30 API SN/ILSAC GF-5 Full Synthetic Oil is formulated to protect against the harsh demands of the current driving environment and provide outstanding engine protection and performance. This SAE 10W-30 API SN/ILSAC GF-5 Full Synthetic Oil protects against leaks, deposits, sludge, and friction within the engine to prolong engine life.

QUALITIES:

- * Extreme temperature performance
- * Better fuel economy
- * Improved emissions system protection
- * Improved high temperature deposit control, foaming/oil aeration, and oil consumption
- * Improved oxidation, sludge control, piston deposit control, and wear properties
- * Provides cleaner engine and better oil pumpability

SPECIFICATIONS: MEETS OR EXCEEDS

ILSAC GF-5
API SN
API SN Resource Conserving
Chrysler MS-6395

TYPICAL PROPERTIES:

Test	Test Method	SAE 10W-30 API SN/ILSAC GF-5 Full Synthetic
Gravity, Specific @ 15.6°C	ASTM D4052	0.853
Viscosity @ 100°C, cSt	ASTM D445	10.5
Viscosity @ 40°C, cSt	ASTM D445	63.3
Viscosity Index	ASTM D2270	155
Viscosity, CCS @ -25°C, cP	ASTM D5293	3730
Pour Point, °C	ASTM D5950	-45
Flash Point, COC, °C	ASTM D92	217
Calcium, mass%	ASTM D4927	0.214
Phosphorus, mass%	ASTM D4927	0.077
Zinc, mass%	ASTM D4927	0.085