



SAE 5W-20 API SN/ILSAC GF-5 Synthetic Oil

DESCRIPTION:

Olympic Petroleum's SAE 5W-20 API SN/ILSAC GF-5 Synthetic Oil contains a detergent additive to prolong engine life. It protects the engine against build up of unwanted sludge, rust and deposits common in stop and go driving. It also provides complete engine protection to minimize wear and extend engine life. Olympic Petroleum's SAE 5W-20 API SN/ILSAC GF-5 Synthetic Oil helps to increase engine efficiency and improve fuel economy.

QUALITIES:

- * Extreme temperature performance
- * Better fuel economy
- * High level of detergency, dispersancy, and oxidation inhibition to control combustion chamber deposits and keep engines clean
- * Anti-wear additives protect critical moving parts
- * Highest quality Group III base stocks

SPECIFICATIONS: MEETS OR EXCEEDS:

- * API SN
- * API SN Resource Conserving
- * ILSAC GF-5

TYPICAL PROPERTIES:

Test	Test Method	SAE 5W-20 API SN/ILSAC GF-5 Synthetic Oil
Gravity, Specific @ 15.6°C	ASTM D4052	0.853
Viscosity @ 100°C, cSt	ASTM D445	8.7
Viscosity @ 40°C, cSt	ASTM D445	49.6
Viscosity Index	ASTM D2270	154
Viscosity, CCS @ -30°C, cP	ASTM D5293	5226
Calcium, mass%	ASTM D4927	0.214
Molybdenum, mass%	ASTM D4927	0.0079
Phosphorus, mass%	ASTM D4927	0.077
Zinc, mass%	ASTM D4927	0.085
TBN	ASTM D2896	7.9