



SAE 5W-30 API SN/ILSAC GF-5 FULL SYNTHETIC

DESCRIPTION:

Olympic Petroleum's SAE 5W-30 API SN/ILSAC GF-5 Full Synthetic is formulated to protect against the harsh demands of the current driving environment and provide outstanding engine protection and performance. This SAE 5W-30 API SN/ILSAC GF-5 Full Synthetic protects against leaks, deposits, sludge, and friction within the engine to prolong engine life.

QUALITIES:

- * Extreme temperature performance
- * Better fuel economy
- * Improved emissions system protection
- * Improved high temperature deposit control, foaming/oil aeration, and oil consumption
- * Improved oxidation, sludge control, piston deposit control, and wear properties
- * Provides cleaner engine and better oil pumpability

SPECIFICATIONS: MEETS OR EXCEEDS

ILSAC GF-5
API SN
API SN Resource Conserving
Ford WSS-M2C946-A, WSS-M2C929-A
Chrysler MS-6395
GM dexos™ 1

TYPICAL PROPERTIES:

Test	Test Method	SAE 5W-30 API SN/ILSAC GF-5 Full Synthetic
Gravity, Specific @ 15.6°C	ASTM D4052	0.849
Viscosity @ 100°C, cSt	ASTM D445	11.0
Viscosity @ 40°C, cSt	ASTM D445	63.9
Viscosity Index	ASTM D2270	165
Viscosity, CCS @ -30°C, cP	ASTM D5293	4850
Pour Point, °C	ASTM D5950	-48
Flash Point, COC, °C	ASTM D92	202
Calcium, mass%	ASTM D4927	0.214
Phosphorus, mass%	ASTM D4927	0.077
Zinc, mass%	ASTM D4927	0.085